

FARBEN SHINE SLIP 248 Slip Agent for Leather Production

Appearance: Grey-white powder

Characteristics: Mixture of inorganic and organic compounds

Concentration (%) : 95.0 ± 2.0

PROPERTIES AND APPLICATION:

-It is a slipping product that used to reduce friction between the skin and drum.

-It helps to prevent damages on the skin due to friction and mechanical effect.

-It makes it easy in the leather processing made with less water. It allows a greater amount of leather loading to drum. Thus saving time and energy.

Recomended usage rates:

In the liming process with less water 0,4 %

Inpickle process 0,4 % (on pelt weight)
Degreasing of sheep pickle pelts 0,4-0,6 % (on pelt weight)

At the beginning of chrome tanning 0,4% (on pelt weight)

Neutralisation 0,3% (on shaved weight)
Retanning, dyeing and fatliquoring 0,3 – 0,5% (on shaved weight)

Vegetable or synthetic tanning 0,4 – 0,6 %

STORAGE:

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING:

25 kg bag.

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others.