



ALPINE RAL 450

Aluminium Based Retanning Agent

Appearance	: White powder
Characteristics	: Aluminium triformate
Al₂O₃ Content (%)	: 21,0 - 25,0
pH Value (10 % in water)	: 3,0 - 5,0

PROPERTIES AND APPLICATION:

- In the production of fur-suede stages of tanning and retanning it is particularly recommended. Improves sanding effect.
- Increasing brightness of and strength of dyes increases the capacity of dyeing. It is suitable for tanning of light color of leather.
- It can be used fixation of waterproof leather around pH 3,5.

Recommended usage rates:

1. and 2. chrome stage for fur-suede 1,0 – 3,0 g/L

In the production of split suede leather using with chrome 2,0-3,0 % provides good sanding fastness.

STORAGE :

In a cool and dry place in original packaging, can be stored for a period of one year. Product must be protected from excessive heat and cold.

PACKAGING :

25 kg bag.

Technical information and recommendations contained herein, is reliable, but conditions and methods of use of our products are beyond our control not imply any warranty. We recommend to use to our customer after identified our products and the suitability of proposals of use. Tips on the use of our products be interpreted in terms of encouraging infringement of patent rights of others

FARBEN DERİ TEKSTİL KONFEKSİYON ve KİMYEVİ MAD. TİC. Ve SAN. A.Ş.

Organize Deri Sanayi Bölgesi 19. Yol 12/6 Parsel Aydınlı Köyü – Tuzla – İSTANBUL / TURKEY

Tel: +90 216 394 11 25 Fax: +90 216 394 11 24

E-mail: info@farben.com.tr, info@herkimgroup.com